



MANUFACTURING SPECIFICATIONS ARCHITECTURAL & DECORATIVE

MATERIAL: ALUMINUM

VIKING

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/2" - .040	60	0.45	1.2	0.04	0.1	0.16	56%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

SURF

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/2" - .051	27	0.6	1.2	0.051	1.2	0.165	63%
	3/4" - .051	43	0.6	1.2	0.081	1.2	0.185	61%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

GALAXIE

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	3/16" - .040	34	0.2	0.812	0.04	0.06	0.099	47%
	1/2" - .051	31	0.42	1.2	0.051	0.1	0.141	57%
	3/4" - .051	36	0.7	2.5	0.051	0.1	0.275	50%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%



MANUFACTURING SPECIFICATIONS ARCHITECTURAL & DECORATIVE

MATERIAL: ALUMINUM

LOUVER

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/8" - .040	44	0.13	0.5	0.04	0.05	0.08	18%
	3/16" - .040	48	0.19	0.75	0.04	0.08	0.175	11%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

SUNSHADE

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	5/16" - .040	38	0.28	0.6	0.04	0.1	0.103	30%
	1/2" - .051	48	0.6	1.2	0.051	0.2	0.219	35%
	1/2" - .081	77	0.6	1.2	0.081	0.2	0.219	35%
	1-1/2" .051	59	1.3	3	0.051	0.5	0.5	21%
	1-1/2" - .081	89	1.3	3	0.081	0.5	0.53	23%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

HONEYCOMB

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .040	21	0.23	0.4	0.04	0.05	0.094	63%
	3/8" - .051	23	0.4	0.75	0.051	0.07	0.133	68%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

* all images are shown in 13ga (0.130) | ©2017 NILES INTERNATIONAL



MANUFACTURING SPECIFICATIONS ARCHITECTURAL & DECORATIVE

MATERIAL: ALUMINUM

RHYTHM

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	5/16" - .040	23	0.3	0.6	0.04	0.06	0.1	60%
	1/2" - .051	21	0.6	1.2	0.051	0.09	0.168	72%
	1/2" - .081	33	0.6	1.2	0.081	0.09	0.185	70%
	1-1/2" - .081	19	1.5	3	0.081	0.12	0.225	82%
	1-1/2" - .125	34	1.5	3	0.125	0.14	0.255	78%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

CHANTILLY

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .032	21	0.22	.375- .750	0.032	0.05	0.09	53%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

CRESCENDO

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/2" - .051	28	0.458	1.0-2.0	0.051	0.089	0.175	61%
	1/2" - .081	45	0.458	1.0-2.0	0.081	0.089	0.175	61%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

* all images are shown in 13ga (0.130) | ©2017 NILES INTERNATIONAL



MANUFACTURING SPECIFICATIONS ARCHITECTURAL & DECORATIVE

MATERIAL: ALUMINUM

CATACOMB

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .051	36	0.25	0.5	0.051	0.07	0.125	49%
	3/8" - .081	45	0.41	0.75	0.081	0.08	0.165	61%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

NETWORK

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .051	36	0.25	0.5	0.051	0.07	0.125	49%
	3/8" - .081	66	0.38	0.75	0.08	0.11	0.2	39%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

PROVINCIAL

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/2" - .081	40	0.52	1.26	0.081	0.09	0.175	73%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%



MANUFACTURING SPECIFICATIONS ARCHITECTURAL & DECORATIVE

MATERIAL: ALUMINUM

ECHO

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .032	21	0.22	.375- .750	0.032	0.05	0.09	53%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

MATERIAL: ALUMINUM

ENCORE

IMAGE*	STYLE	LBS. PER 100 sq ft	DESIGN		STRAND		OVERALL THICKNESS	OPEN AREA
			SWD	LWD	THICKNESS	WIDTH		
	1/4" - .040	21	0.275	1.125	0.04	0.05	0.078	70%
TOLERANCES		MINIMUM	+/- 5%	ABSOLUTE	MINIMUM	+/- 5%	+/- 10%	+/- 10%

* all images are shown in 13ga (0.130) | ©2017 NILES INTERNATIONAL